

L32 ANSWER 9 OF 15 WPINDEX COPYRIGHT 2000 DERWENT INFORMATION LTD
AN 1997-084300 [08] WPINDEX *In Japanese
CR 1991-040734 [06]; 1996-185729 [19]; 1996-185730 [19]
DNN N1997-069684

TI Exterior finish method for building using e.g. ALC board, asbestos cement plate, inorganic siding board, concrete block - by utilising adhesive with 5 percent or more stretch after hardening in sticking flexible exterior sheet on exterior wall of building.

DC Q45
PA (KIKS) KIKUSUI KAGAKU KOGYO KK
CYC 1
PI JP 08326259 A 19961210 (199708)* 4p
JP 2963873 B2 19991018 (199949) 3p
ADT JP 08326259 A Div ex JP 1989-128421 19890522, JP 1996-140662 19890522; JP 2963873 B2 Div ex JP 1989-128421 19890522, JP 1996-140662 19890522
FDT JP 2963873 B2 Previous Publ. JP 08326259
PRAI JP 1989-128421 19890522; JP 1996-140662 19890522
AB JP 08326259 A UPAB: 19991124

In finishing an exterior part, e.g. asbestos-cement board, inorganic siding plate, or concrete blocks as outer wall, etc., a flexible decorated sheet, e.g., non-woven fabrics coated with an aq. paint with a filler, a pigment, etc., through an acrylic resin emulsion is bonded to the surface of outer wall.

Pref. flexible decorated sheet has an elongation of 2% or more, esp. 5% or more after hardening of the binder and also has a water permeability of 0.5 ml/24 hrs. or less. The sheet is bonded over 5 mm or more as lap allowance.

USE/ADVANTAGE - The method can effectively finish the exterior parts of building without forming joints.
Dwg.0/0